

Aluminum

Aluminum Fuel Caps

- Attractive and durable aluminum castings.
- Safety venting features:
 - high capacity pressure relief (5-10 psig)
 - high capacity thermal relief (225°-235°F)
- Special compound gasket for tight seal.
- 12" chain and cross-bar combination prevent loss of cap while refueling.



2" Dia. Aluminum Fuel Caps (Female Thread)

Sloan No.	Measurement Across Threads	Cross-Bar Length	Thread Type	Lock	Venting
431084	2.25"	3.25"	11.5NPSM	no	vented



2-1/2" Dia. Aluminum Fuel Caps (Female Thread)

Sloan No.	Measurement Across Threads	Cross-Bar Length	Thread Type	Lock	Venting
431085	2.37"	3.25"	8 UN	no	vented



3" Dia. Aluminum Fuel Caps (Female Thread)

Sloan No.	Measurement Across Threads	Cross-Bar Length	Thread Type	Lock	Venting
431086	3.37"	7.5"	8 NPSL	no	vented
431087	3.37"	7.5"	8 NPSL	yes	vented
431088	3.43"	7.5"	5-1/2 Special	no	vented
431089	3.43"	7.5"	5-1/2 Special	yes	vented



4" Dia. Aluminum Fuel Caps (Female Thread)

Sloan No.	Measurement Across Threads	Cross-Bar Length	Thread Type	Lock	Venting
431090	4.37"	7.5"	8NPSM	no	vented
431091	4.37"	7.5"	8NPSM	yes	vented

Brass

Brass Fuel Caps

- All brass castings for years of corrosion-free performance.
- Fusible elements, in case of fire, melt at 190°F.
- Quality locking feature maintains secure fastening of fuel tank cap to tank.
- All locking caps provided with two keys.
- Available vented or non-vented.
- 8.5" chain and cross-bar combination prevent loss of cap while refueling.
- Most vehicles built before October 1985 have non-vented fuel tanks. Because of the possibility of vapor lock, non-vented fuel caps should not be installed on them.

Brass Fuel Cap Gaskets (1/8" Dia.)

Sloan No.	Usage
431702	431000, 431002
431715	431008, 431009, 431012
431717	431010, 431011, 431015
431718	431013, 431014
431721	431018
431731	431005, 431006



2" Dia. Brass Fuel Caps (Female Thread)



Sloan No.	Measurement Across Threads	Cross-Bar Length	Thread Type	Lock	Venting
431008	2.3"	3-1/2"	11-1/2 NPSM	no	vented
431009	2.3"	3-1/2"	11-1/2 NPSM	no	non-vented
431012	2.3"	3-1/2"	11-1/2 NPSM	yes	vented
431124	2.3"	14" (External)	11-1/2 NPSM	no	non-vented

External Cord



2-1/8" Dia. Brass Fuel Caps (Male Thread)

Sloan No.	Measurement Across Threads	Cross-Bar Length	Thread Type	Lock	Venting
431010	2.125"	3-1/2"	12 UN male	no	vented
431011	2.125"	3-1/2"	12 UN male	no	non-vented
431015	2.125"	3-1/2"	12 UN male	yes	vented



2-1/2" Dia. Brass Fuel Caps (Female Thread)

Sloan No.	Measurement Across Threads	Cross-Bar Length	Thread Type	Lock	Venting
431013	2.5"	3-1/2"	8 UN	yes	non-vented
431014	2.5"	3-1/2"	8 UN	no	non-vented

Brass



3-1/2" Dia. Brass Fuel Caps (Female Thread)

Sloan No.	Measurement Across Threads	Cross-Bar Length	Thread Type	Lock	Venting
431018	3.5"	8"	5-1/2 Special	no	vented



4" Dia. Brass Fuel Caps (Female Thread)

Sloan No.	Measurement Across Threads	Cross-Bar Length	Thread Type	Lock	Venting
431005	4.3"	8"	8 NPSM	no	non-vented
431006	4.3"	8"	8 NPSM	yes	non-vented



4-1/4" Dia. Brass Fuel Caps (Male Thread)

Sloan No.	Measurement Across Threads	Cross-Bar Length	Thread Type	Lock	Venting
431000	3.7"	8"	12 UN	no	non-vented
431002	3.7"	8"	8 UN	no	non-vented